

\*\*\*SPARE PART\*\*\* SIPLUS ET200S F-DI 24V PROFISAF -25 ...  
 +60 DEGREES C WITH CONFORMAL COATING BASED ON  
 6ES7138-4FA04-0AB0



Figure similar

Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> <li>• 24 V DC</li> </ul>	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	No
Encoder supply	
Number of outputs	2
Type of output voltage	min. L+ (-1.5 V)
Short-circuit protection	Yes; Electronic (response threshold 0.7 A to 1.8 A)
Output current	
<ul style="list-style-type: none"> <li>• Rated value</li> <li>• permissible range, lower limit</li> <li>• max.</li> </ul>	300 mA 0 mA 300 mA
Power loss	
Power loss, typ.	4 W

Address area	
Occupied address area	
• Inputs	6 byte
• Outputs	4 byte
Digital inputs	
Number of digital inputs	8; 8 single channel, 4 two-channel
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
• Number of simultaneously controllable inputs	8
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-30 to +5V
• for signal "1"	+15 to +30V
Input current	
• for signal "1", typ.	3.7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes
— at "0" to "1", min.	0.3 ms
— at "0" to "1", max.	17 ms
— at "1" to "0", min.	0.3 ms
— at "1" to "0", max.	17 ms
Cable length	
• shielded, max.	200 m
• unshielded, max.	200 m
Encoder	
Connectable encoders	
• 2-wire sensor	No
Interrupts/diagnostics/status information	
Diagnostic functions	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnostic messages	
• Diagnostic information readable	Yes
• Short-circuit	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital input (green)	Yes

Potential separation	
Potential separation digital inputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	No
Permissible potential difference	
between M internally and the inputs	75 V DC/60 V AC
Isolation	
Isolation tested with	500 V DC
Standards, approvals, certificates	
CE mark	Yes
Highest safety class achievable in safety mode	
• acc. to EN 954	Cat. 3 (single-channel), Cat. 4 (two-channel)
• Performance level according to ISO 13849-1	e
• SIL acc. to IEC 61508	SIL 2 (single-channel), SIL 3 (two-channel)
Ambient conditions	
Ambient temperature during operation	
• min.	-25 °C; = Tmin
• max.	60 °C; = Tmax
Extended ambient conditions	
• relative to ambient temperature-atmospheric pressure-installation altitude	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m)
Relative humidity	
— With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
— against biologically active substances / conformity with EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— against chemically active substances / conformity with EN 60721-3-3	Yes; Class 3C4 (RH < 75%) incl. salt spray according to EN 60068-2-52 (degree of severity 3). The supplied connector covers must remain on the unused interfaces during operation!
— against mechanically active substances / conformity with EN 60721-3-3	Yes; Class 3S4 incl. sand, dust. The supplied connector covers must remain on the unused interfaces during operation!
Dimensions	
Width	30 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	78 g
<b>last modified:</b>	05/31/2017