SIEMENS

Data sheet	6GK7443-5FX01-0XE0
Product type designation	CP 443-5 Basic SIMATIC NET, CP 443-5 BASIC COMMUNICATIONS PROCESSOR FOR CONNECTING SIMATIC S7-400 TO PROFIBUS, FMS, S5- COMPATIBLE PG/OP AND S7 COMMUNICATION
Transmission rate	
Transfer rate	
• at the 1st interface / acc. to PROFIBUS	9.6 kbit/s 12 Mbit/s
Interfaces	
Number of interfaces / acc. to Industrial Ethernet	0
Number of electrical connections	
 at the 1st interface / acc. to PROFIBUS 	1
Type of electrical connection	
• at the 1st interface / acc. to PROFIBUS	9-pin Sub-D socket (RS485)
Supply voltage, current consumption, power loss	3
Type of voltage / of the supply voltage	DC
Supply voltage / 1 / from backplane bus	5 V
Supply voltage	5 V
Relative symmetrical tolerance / at DC	
• at 5 V	5 %
Power loss [W]	6.5 W
Ambient conditions	
Ambient temperature	
 during operation 	0 60 °C
• during storage	-40 +70 °C
 during transport 	-40 +70 °C
Relative humidity	
 at 25 °C / without condensation / during operation / maximum 	95 %
Protection class IP	IP20
Design, dimensions and weight	
Module format	Compact module S7-400 single width
Width	25 mm
Height	290 mm
Depth	210 mm
Net weight	0.7 kg
Product properties functions components/gen	oral

Product properties, functions, components / general

Number of units		
• per CPU / maximum	14	
Note	depending on CPU type	
Performance data / open communication		
Number of possible connections / for open communication / by means of SEND/RECEIVE	32	
blocks / maximum		
Amount of data		
 as user data per connection / for open 	240 byte	
communication / by means of SEND/RECEIVE		
blocks / maximum		
Performance data / FMS functions		
Number of possible connections / for FMS	48	
connection / maximum		
Amount of data / of the variables		
 for READ job / maximum 	237 byte	
 for WRITE job / maximum 	233 byte	
Number of variables		
 Configurable from server to FMS partner 	512	
 Loadable from server to FMS partner 	2640	
Performance data / S7 communication		
Number of possible connections / for S7		
communication		
• maximum	48	
Performance data / multi-protocol mode		
Number of possible connections / of which 2	59	
reserved for PG/OP communication / with multi-		
protocol mode / maximum		
Product functions / management, configuration		
Configuration software		
• required	STEP 7 V5.1 SP1 or higher and NCM S7 for PROFIBUS	
Further Information / Internet Links		
Internet-Link		
 to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst	
• to website: Industrial communication	http://www.siemens.com/simatic-net	
• to website: Industry Mall	https://mall.industry.siemens.com	
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter	
 to website: Image database 	http://automation.siemens.com/bilddb	
 to website: CAx Download Manager 	http://www.siemens.com/cax	
• to website: Industry Online Support	https://support.industry.siemens.com	

Security information	
Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third- party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	08/12/2019

08/13/2019