

Product description

PROFIBUS bus connector, RS 485, screw, with PG socket, 90° SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s 90° cable outlet, 15.8x 64x 35.6 mm (WxHxD), terminating resistor with isolating function, With PG receptacle



Transfer rate

Transfer rate / with PROFIBUS DP	9.6 kbit/s ... 12 Mbit/s
----------------------------------	--------------------------

Interfaces

Number of electrical connections	
• for PROFIBUS cables	2
• for network components or terminal equipment	1
Type of electrical connection	
• for PROFIBUS cables	Screw
• for network components or terminal equipment	9-pin Sub-D connector
Type of electrical connection / FastConnect	No

Mechanical data

Design of terminating resistor	Integrated resistor combination that can be selected with slide switch
Material / of the enclosure	plastic
Locking mechanism design	Screw

Design, dimensions and weights

Type of cable outlet	90 degree cable outlet
----------------------	------------------------

Width	15.8 mm
Height	64 mm
Depth	35.6 mm
Net weight	10 g

Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> during operation 	0 °C
<ul style="list-style-type: none"> during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> during transport 	-40 ... +70 °C
Protection class IP	IP20

Product features, product functions, product components / general

Product feature	
<ul style="list-style-type: none"> silicon-free 	Yes
Product component	
<ul style="list-style-type: none"> PG connection socket 	Yes
<ul style="list-style-type: none"> strain relief 	Yes

Standards, specifications, approvals

Certificate of suitability	
<ul style="list-style-type: none"> RoHS conformity 	Yes
<ul style="list-style-type: none"> UL approval 	Yes
Reference code	
<ul style="list-style-type: none"> acc. to DIN EN 81346-2 	XF

last modified: 08/18/2020